

CLG-60 Series

60W Single Output LED Lighting PSU



FEATURES

- Universal AC input / full range
- Short circuit / Overload / Over-voltage / Over-temperature protections
- Built-in active PFC function
- IP67 design for indoor or outdoor installations
- UL1310 Class 2 power unit
- Cooling by free air convection
- 100% full load burn-in test
- High reliability
- Suitable for LED lighting and moving sign applications
- 20V, 27V & 36V versions available

ENVIRONMENTAL

Operating Temp: -30 to +70°C (with de-rating)

Storage Temp: -40 to +80°C


SAFETY / EMC

UL1310 Class 2
CAN/CSA C22.2 No. 223-M91 (except 48V)
EN61347-1
EN61347-2-13
IP67 approved

EN55015
EN55022 (CISPR22) Class B
EN61000-3-2,-3
EN61000-4-2, 3, 4, 5, 6, 8, 11
ENV50204
EN55024
EN61547
Light industry level, criteria A

ELECTRICAL SPECIFICATIONS

Model No.	CLG-60-XX			
XX	12	15	24	48
AC Input	90-264VAC, Single Phase, 47-63Hz			
Power Factor	PF>0.9/230Vac		PF>0.98/115Vac at full load	
DC Output				
Voltage	12V	15V	24V	48V
Current	0-5A	0-4A	0-2.5A	0-1.3A
Rated Power	60W	60W	60W	62.5W
Ripple & noise (p-p) (2)	2V	2.4V	2.7V	4.6V
Voltage Tolerance (3)	±10%			
Line Regulation	±4%			
Load Regulation	±10%			
Overload	95-110%	130% (max)		
	Constant I limiting. Recovers automatically when fault removed.			
Over Voltage	13.8-16V	17.5-21V	28-32V	54-60V
	Shut down output voltage. Re-power on to recover.			
Over Temperature	Shut down output voltage. Recovers automatically after temp goes down.			
Dimensions	172(L) x 61.5(W) x 39(H)mm			
Weight	0.86Kg			
Notes:	<ol style="list-style-type: none"> 1. All parameters <i>NOT</i> specially mentioned are measured at 230VAC input, rated load and 25°C ambient temperature. 2. Ripple and noise are measured at 20MHz bandwidth by using a 12" twisted pair wire terminated with a 0.1µF and 47µF parallel capacitor. 3. Tolerance includes set up tolerance, line and load regulation. 4. De-rating may be needed under low input voltage conditions. Consult sales for more details. 			



Specifications subject to change without notice

Safety Power Group Ltd

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565

Fax: +44 (0) 1252 546021

e-mail: sales@safety-power.com

web: www.safety-power.com