

DRT-960 Series

960W Single Output DIN Rail Power Supplies



FEATURES

- Three phase AC 340-550V wide range input
- Short circuit, overload, over voltage, over temperature protected
- Optional parallel function (1+1)
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- UL508 (industrial control equipment) approved
- EN61000-6-2 (EN50082-2) industrial immunity level
- 100% full load burn-in test
- 3 year warranty

ENVIRONMENTAL

Operating Temp: -20 to +60°C (with de-rating)

Storage Temp: -40 to +85°C

SAFETY / EMC (SEE NOTE 4)

EN60950
UL60950
UL508

EN55011 (CISPR11)
EN55022 (CISPR22)
EN61204-3 Class B
EN61000-3-2, -3
EN61000-4-2, 3, 4, 5, 6, 8, 11
ENV50204
EN61204-3
EN61000-6-2 (EN50082-2)
Heavy industry level, criteria A



ELECTRICAL SPECIFICATIONS

Model No.	DRT-960-XX	
XX	24	48
AC Input	340-550VAC, 3 Phase, 47-63Hz	
DC Output		
Voltage	24V	48V
Current	0-40A	0-20A
Rated Power	960W	960W
Ripple & noise (p-p)	80mV	80mV
Voltage Tolerance	±1.0%	±1.0%
Line Regulation	±0.5%	±0.5%
Load Regulation	±0.5%	±0.5%
Overload	Constant I limiting. Shut down O/P volts after 3 sec. Re-power on to recover	
Over Voltage	Shuts down O/P volts. Re-power on to recover	
Over Temperature	Shuts down O/P volts. Recovers automatically when temp goes down	
Dimensions	276(W) x 125.2(H) x 100(D)mm	
Weight	3.3Kg	

- Notes:**
1. All parameters *NOT* specially mentioned are measured at 230VAC input, rated load and 25°C ambient temperature.
 2. Ripple and noise are measured at 20MHz bandwidth by using a 12" twisted pair wire terminated with a 0.1µF and 47µF parallel capacitor.
 3. Tolerance includes set up tolerance, line and load regulation.
 4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.

Specifications subject to change without notice

Safety Power Group Ltd

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565

Fax: +44 (0) 1252 546021

e-mail: sales@safety-power.com

web: www.safety-power.com