

LD1007 Series

8.4W DC to DC Switching Power Supply



FEATURES

- DC output with Constant Current
- Outdoor or indoor use
- Waterproof design - IP66 for dry / damp locations
- Convection cooled in plastic housing

ENVIRONMENTAL

Operating Temp: -30 to +50°C

Storage Temp: -40 to +85°C

SAFETY / EMC

EMC meet FCC & CE

ELECTRICAL SPECIFICATIONS

DC Input	10.5~30VDC / 1A
Efficiency	85% Typical
Protections	OPP, SCP - Auto-recovery
Dimensions	46(L) x 34(W) x 19(H)mm
Weight	65grams

MODEL LISTINGS

Model	DC Output Constant Voltage	Output Current Max.	Watts Max.
LD1007-12	12V ±5%	700mA	8.4W
LD1007-24	24V ±5%	350mA	8.4W

Model	DC Output (Vf) Forward Voltage	Output Constant Current	Watts Max.
LD1007-12-C0700	2~12V	700mA ±5%	8.4W
LD1007-24-C0350	2~24V	350mA ±5%	8.4W

Specifications subject to change without notice

Ledlite-Power

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565

Fax: +44 (0) 1252 546021

e-mail: sales@ledlite-power.com

web: www.ledlite-power.com