

LD1026 Series

25W DC to DC Switching Power Supply

FEATURES

- DC output with Constant Current
- Outdoor or indoor use
- Waterproof design - IP66 for dry / damp locations
- Convection cooled in plastic housing

ENVIRONMENTAL

Operating Temp: -30 to +50°C

Storage Temp: -40 to +85°C

SAFETY / EMC

EMC meet FCC & CE

ELECTRICAL SPECIFICATIONS

DC Input	10~30VDC / 3.5A
Efficiency	85% Typical
Protections	OPP, SCP - Auto-recovery
Dimensions	85(L) x 35(W) x 23(H)mm
Weight	120grams typical

MODEL LISTINGS

Model	DC Output Constant Voltage	Output Current Max.	Watts Max.
LD1026-12	12V ±5%	2100mA	25W
LD1026-18	18V ±5%	1400mA	25W
LD1026-24	24V ±5%	1050mA	25W
LD1026-36	36V ±5%	700mA	25W

Model	DC Output (Vf) Forward Voltage	Output Constant Current	Watts Max.
LD1026-12-C2100	2~12V	2100mA ±5%	25W
LD1026-18-C1400	2~18V	1400mA ±5%	25W
LD1026-24-C1050	2~24V	1050mA ±5%	25W
LD1026-36-C0700	2~36V	700mA ±5%	25W

Specifications subject to change without notice

Ledlite-Power

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565

Fax: +44 (0) 1252 546021

e-mail: sales@ledlite-power.com

web: www.ledlite-power.com