


LLP6

High Power LED Streetlight



BENEFITS

- Low Power Consumption - 168W
- High Brightness - Up to 12600 Lumens, 8 times that of incandescent lamps
- Long Life - Up to 50,000 Hours
- Robust Design - Shock and vibration resistant
- Light Beam - Low heat generated / no UV radiation
- Easy Installation - Adjustable hoop, can be easily installed on most types of lamp pole
- Save Money - Reduces labour and maintenance costs

SPECIAL FEATURES

- Slim profile - reduces weight and the force exerted by the wind to reduce lamp pole loading
- Unique integrated lens and lampshade design.
- Energy Saving - together with the high efficiency power supply will save 50 - 80% energy than conventional sodium and mercury lamps
- Start Without Delay - reaches normal brightness without delay associated with traditional street lamps
- Environmental Protection - no lead or mercury, therefore no environmental pollution

APPROVALS

CE
UL
RoHS

MAIN SPECIFICATIONS

Input Voltage	85-264Vac 47-63Hz
Power Factor	>0.9
Total Harmonic Dist.	<20%
Power Efficiency	85%
Working Voltage	24VDC
LED Consumption	168W
PSU Consumption	30W
LED Luminous Eff.	>80lm/W
LED Initial Flux	15,000lm (Tj=25°C)
LED Maintain Flux	14,000lm (Tj=70°C, Ta=25°C)
Lamp Output Flux	12,600lm (Tj=70°C, Ta=25°C)
Lamp Efficiency	>90%
	(Height =6M) >80lux (equal to HPS 200lux)
	(Height =8M) >45lux (equal to HPS 113lux)
	(Height =10M) >28lux (equal to HPS 70lux)
	(Height =12M) >20lux (equal to HPS 50lux)
	20 x 8M (Height = 6M)
	26 x 10M (Height = 8M)
	33 x 13M (Height = 10M)
	40 x 16M (Height = 12M)
	Pure white: 5,000-7,000K
	Warm White: 3,000-4,000K
Effective Illuminated Area	
Colour Temp.	
CRI	Ra>75
Working Temp.	-30°C ~ 50°C
Working Humidity	10 - 90% RH
IP Rating	IP65
Dimensions	890(L) x 315(W) x 90(H)mm
Weight	13Kg

Specifications subject to change without notice

Ledlite-Power

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565 Fax: +44 (0) 1252 546021

e-mail: sales@ledlite-power.com web: www.ledlite-power.com