

PB-360 Series

360W Single Output Battery Charger



FEATURES

- AC input range switch selectable
- Built-in passive PFC (option)
- 3 stage charging
- Charger for lead acid batteries
- Short circuit protection
- Reverse polarity protection
- Over Voltage protection
- Over Temperature protection
- Temp. controlled cooling fan
- 2 colour LED indicator
- 2 years warranty

ENVIRONMENTAL

Operating Temp: -20 to +60°C

Storage Temp: -40 to +85°C

SAFETY / EMC (SEE NOTE 4)

EN60335-2-29 CB approved by TUV

EN55022 (CISPR22) Class B
EN61000-3-2,-3 (P type only)
EN61000-4-2, 3, 4, 5, 6, 8, 11
ENV50204
EN55024
Light Industry level criteria A

ELECTRICAL SPECIFICATIONS

Model No.	PB-360-X-12	PB-360-X-24
X	P: With Passive PFC / N: Without Passive PFC	
AC Input	90-132 / 180-264VAC switch selectable, 47-63Hz	
DC Output		
Boost Charge Volts	14.4V	28.8V
Float Charge Volts	13.6V	27.2V
Output Current	24.3A	12.5A
Battery Capacity (note 5)	80-200Ahr	40-125Ahr
Remote Control	Open: Normal working / Short: Stop charging	
Protection		
Overload	90 - 110% of rated output current. Constant I limiting. Recovers automatically.	
Over Voltage	15 - 17V	30 - 35V
Over Temperature	Shut down output. Re-power on to recover.	
Reverse Polarity	Automatically de-rates charge current until zero. By internal fuse.	
Dimensions	253(L) x 135(W) x 48.5(H) mm	
Weight	1.5Kg	

- Notes:**
1. All parameters **NOT** specially mentioned are measured at 230VAC input, rated load and 25°C ambient temperature.
 2. Ripple and noise are measured at 20MHz bandwidth by using a 12" twisted pair wire terminated with a 0.1µF and 47µF parallel capacitor.
 3. Tolerance includes set up tolerance, line and load regulation.
 4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.
 5. Please consult your battery manufacturer for their recommendations about maximum charging current limitations.

Specifications subject to change without notice

Safety Power Group Ltd

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565

Fax: +44 (0) 1252 546021

e-mail: sales@safety-power.com

web: www.safety-power.com